



# ARC CBM Low Head D™ Product Data Sheet

**Delivering Tomorrow's Fluid Technologies Today**

## Description

**Foamer, Micro-emulsion, Shale Stabilizer**

**ARC CBM Low Head D™** is a combination of a foamer and micro-solution for the purpose of treating coal or shale wells. The foamer also acts as a corrosion inhibitor.

## Properties

Form:	Liquid	Chemical Family:	A chemical blend
Color:	Yellow	Solubility:	Complete in water
Odor:	Citrus	Wt. per Gal.:	8.35 lbs.
Freezing Point:	< 5° F	Flash Point:	90° F

## Application

**ARC CBM Low Head D™ is for coal and shale reservoir applications .**

It is suggested to use **ARC CBM Low Head D™** at 6 – 10 gallons per 20 bbls of make up water. The actual concentration required will depend on the make up water. So this is a well site call.

If further stiffening of the foam is required use **ARC CBM PCS™** at 1 – 2 quarts per 20 bbls of make-up water with **ARC CBM Low Head D™**.

## Compatibility

**ARC CBM Low Head D™ is ideal for coalbed drilling.**

**ARC CBM Low Head D™** is compatible with nonionic and cationic corrosion inhibitors.

## Handling and Storage

**\* Refer to Material Safety Data Sheet . . .**

Avoid contact with eyes, skin and clothing. Avoid breathing vapors. Store away from heat, sparks and open flames. Refer to the Material Safety Data Sheet for more detailed information.

## Packaging

Specialty packaging is available . . .

**ARC CBM Low Head D™** is available in 5 gal. pails, 55-gal drums and 330-gal totes.

## Questions & Answers

ARC Fluid Technologies, LLC "Offering You Tomorrow's Solutions Today"

If you would like to know more about the ARC Micro-solution Technologies and how it can improve your well performance please contact us at:

ARC Fluid Technologies, LLC

P.O. Box 6669

Kingwood, Texas

USA 77325-6669

Continental USA and Canada Toll Free: +1-1-866-800-8016

24 Hours:

+1-713-331-0534

Fax:

+1-281-360-6959

E-mail:

[arcsolutions@arcfluids.com](mailto:arcsolutions@arcfluids.com)

Web:

[www.arcfluids.com](http://www.arcfluids.com)

***No claim of personal safety is intended nor implied by the use of the name Safe in this product. Personnel handling this material should read and follow all safety and handling procedures set forth on the Material Safety Data Sheet.***